

TECHNICAL DATA SHEET



SEMI-SYNTHETIC SAE 10W-40

**PRODUCT # 10172, 10176, 10205,
10218, 10221, 10227, 10373**

TEST

ASTM

TYPICAL

API Gravity	D-1298	32.1
Specific Gravity @ 60°F	D-1298	.8649
Density @ 60°F LBS/US Gal	D-1298	7.202
Viscosity @ 40°C cSt	D-445	97
Viscosity @ 100°C cSt	D-445	15.0
VI		163
Flash Point, COC °F	D-92	410
Color		Amber
Zinc, Wt. %		.12

Lucas Semi Synthetic SAE 10W-40 is a blend of high quality base stocks and an exclusive high performance additive package that ensures minimum drag, extended engine life, longer oil life and easy cold weather starting.

Designed for use in both gasoline and automotive diesel engines.

The exclusive additive package in Lucas Semi Synthetic SAE 10W-40 allows for extended drain periods.

Lucas Semi Synthetic SAE 10W-40 is excellent for use in turbo charged engines. The user can expect longer oil life and lower oil temperature.

Meets or exceeds all manufacturers specifications for A3/B3/B4 and API SM/SL/SJ/CF. Exceeds VW 502/505/500 and Ford WSS M2 C 917 A.